

**A07164 PM CAN MASS AF SENSOR #7164 16n11**

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A07164 PM CAN MASS AF SENSOR #7164 16n11

Material number : 00000000001046415

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers**
**For SDS Information** : Compliance Services 1-877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

**SECTION 2. HAZARDS IDENTIFICATION**
**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	aliphatic, solvent-like

**GHS Classification**

Flammable aerosols : Category 1  
 Gases under pressure : Compressed gas  
 Skin irritation : Category 2  
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
 P210 Keep away from heat/sparks/open flames/hot surfaces.  
 No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after

## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/container in accordance with local regulation.

**Potential Health Effects****Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 50 - < 70
butane	106-97-8	>= 20 - < 30
ethanol	64-17-5	>= 5 - < 10
propane	74-98-6	>= 5 - < 10
heptane	142-82-5	>= 1 - < 5

**SECTION 4. FIRST AID MEASURES**

**A07164 PM CAN MASS AF SENSOR #7164 16n11**

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

---

- General advice : Show this safety data sheet to the doctor in attendance.
- If inhaled : Remove to fresh air.  
Call a physician or poison control centre immediately.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Drink 1 or 2 glasses of water.  
Obtain medical attention.
- 

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods :
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for : Wipe up with absorbent material (e.g. cloth, fleece).
-

## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

containment and cleaning up

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.  
Do not puncture.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store together with oxidizing and self-igniting products.
- Storage temperature : < 48.8 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
heptane	142-82-5	TWA	85 ppm	NIOSH REL

## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

			350 mg/m <sup>3</sup>	
		C	440 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
		STEL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA P0

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
In the case of dust or aerosol formation use respirator with an approved filter.
- Hand protection  
Material : Neoprene  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Aerosol containing a liquefied gas
- Colour : clear
- Odour : aliphatic, solvent-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Boiling point : Not applicable
- Flash point :  
No data available
- Evaporation rate : not determined
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit : not determined

**A07164 PM CAN MASS AF SENSOR #7164 16n11**

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

Lower explosion limit	: not determined
Vapour pressure	: 1,379 - 2,068.4 hPa (21 °C)
Relative vapour density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: partly soluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Components:****butane:**

Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h
	: LC50 Rat: 1,355 mg/l

**ethanol:**

Acute oral toxicity	: LD50 Oral Rat: 7,060 mg/kg
---------------------	------------------------------

## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l  
Exposure time: 4 h

**propane:**

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 Rat: 658 mg/l  
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

**heptane:**

Acute inhalation toxicity : LC50 Rat: 103,000 mg/l  
Exposure time: 4 h

**Skin corrosion/irritation****Product:**

Remarks: slight irritation

**Serious eye damage/eye irritation****Product:**

Remarks: slight irritation

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**Naphtha (petroleum), hydrotreated light:**

**butane:**

**ethanol:**

**propane:**

**heptane:**

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

No data available

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

**Components:****butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

**heptane :**

Partition coefficient: n-octanol/water : log Pow: > 3.0

log Pow: 5

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., May cause long lasting harmful effects to aquatic life.



**A07164 PM CAN MASS AF SENSOR #7164 16n11**

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, 2.1, - Limited quantity

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** WARNING! This product contains a chemical known to the

## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015


benzene	State of California to cause cancer.	71-43-2
	WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
toluene		108-88-3
benzene		71-43-2

**The components of this product are reported in the following inventories:**

<b>TSCA</b>	On TSCA Inventory
<b>DSL</b>	All components of this product are on the Canadian DSL
<b>AICS</b>	On the inventory, or in compliance with the inventory
<b>NZIoC</b>	Not in compliance with the inventory
<b>PICCS</b>	On the inventory, or in compliance with the inventory
<b>IECSC</b>	On the inventory, or in compliance with the inventory

**Inventory Acronym and Validity Area Legend:**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA GHS Label Information:**

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness.

Precautionary statements

:

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves.

**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

# SAFETY DATA SHEET



## A07164 PM CAN MASS AF SENSOR #7164 16n11

Version 3.0

Revision Date 08/31/2015

Print Date 11/25/2015

POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	3.0
Revision Date:	08/31/2015
Print Date:	11/25/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.