

<b>ASHLAND®</b>		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : PARTS Master® SAE 20W-50  
MOTOR OIL

### Recommended use of the chemical and restrictions on use

<b>Details of the supplier of the safety data sheet</b> Ashland P.O. Box 2219 Columbus, OH 43216 United States of America  EHS Customer Requests@ashland.com	<b>Emergency telephone number</b> 1-800-ASHLAND (1-800-274-5263)  <b>Regulatory Information Number</b> 1-800-325-3751  <b>Product Information</b> 614-790-3333
--	---

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

### Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.22

<b>ASHLAND®</b>		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

---

#### SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

---

#### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

<b>ASHLAND</b>		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

for firefighters

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

---

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

- Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

<b>ASHLAND®</b>		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

Skin and body protection : Wear as appropriate:  
 Safety shoes  
 Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 390 °F / > 199 °C  
 Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)  
 Calculated Explosive Limit

Lower explosion limit : 1 %(V)  
 Calculated Explosive Limit

Vapour pressure : 0.0133333 hPa (21.11 °C)  
 Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.8834 g/cm<sup>3</sup> (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition :

<b>ASHLAND®</b>		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 171 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

**Components:**

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Not irritating to skin

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Unlikely to cause eye irritation or injury.

<b>ASHLAND®</b>		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

**Components:**

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

<b>ASHLAND®</b>		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

---

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

Not dangerous goods

**U.S. DOT - RAIL**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TRANSPORT CANADA - ROAD**

Not dangerous goods

**TRANSPORT CANADA - RAIL**

Not dangerous goods

**TRANSPORT CANADA - INLAND WATERWAYS**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

<b>ASHLAND®</b>		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313 Component(s)** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	5.00 - 10.00 %

**New Jersey Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	5.00 - 10.00 %
POLYOLEFIN AMIDE ALKENEAMINE	Not Assigned	1.00 - 5.00 %
LUBRICANT ADDITIVE	Not Assigned	1.00 - 5.00 %

**California Prop 65** Proposition 65 warnings are not required for this product



<b>ASHLAND®</b>		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : On the inventory, or in compliance with the inventory
- ENCS : q (quantity restricted)
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : q (quantity restricted)

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 05/22/2015

<p><b>NFPA:</b></p> <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow; color: black;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements referred to under sections 2 and 3.**

H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

<b>ASHLAND®</b>		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

Ashland internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency

<b>ASHLAND®</b>		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 05/22/2015
		Print Date: 6/11/2015
		SDS Number: R0171982
PARTS Master® SAE 20W-50 MOTOR OIL		Version: 1.0
PM5135		

RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System