



Safety Data Sheet

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PartsM 5W20 SB SNGF5 55G
Product Code: PMI52B55
Emergency Phone: CHEMTREC: +1 (800) 424-9300
 International: +01 (703) 527-3887
Poison Control Center: (800) 222-1222
Company: Warren Distribution, Inc.
 727 S. 13th Street
 Omaha, NE 68102
Information Phone: +01 (800) 825-1235 +01 (402) 341-9397
E-mail: sds@wd-wpp.com

II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact, Inhalation, Ingestion, Eye contact
Target Organs: No organs known to be damaged from exposure to this product.
Chemical Interactions: No chemical interaction known to affect toxicity.
Conditions Aggravated by Exposure: Personnel with pre-existing skin disorders should avoid contact with this product.

Acute Health Effects:

Inhalation Irritation: Breathing oil mist in concentrations that exceed the TLV and PEL may result in respiratory discomfort and irritation.
Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption: No absorption hazard in normal industrial use.
Eye Contact: No hazard in normal industrial use.
Ingestion Irritation: Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

Chronic Health Effects:

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

HMIS Ratings:

Health: 1
 Fire: 1
 Reactivity: 0
 PPE: B

NFPA Ratings:

Health: 1
 Fire: 1
 Reactivity: 0

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Petroleum distillates, hydrotreated heavy paraffinic	30 - 60	64742-54-7	5 mg/m3
Petroleum distillates, solvent dewaxed heavy paraffinic	10 - 30	64742-65-0	5 mg/m3
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	7 - 13	72623-87-1	5 mg/m3

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

Safety Data Sheet

IV. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eyes:	Use eye wash to remove a chemical from the eye. Flush the affected eye for at least fifteen minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention if irritation persists.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists. Seek medical advice if symptoms persist.
Ingestion:	Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this SDS.
Notes to Doctor:	Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

V. FIRE FIGHTING MEASURES

Flammability Summary:	Combustible at elevated temperatures
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.
Hazardous Combustion Products:	Carbon monoxide, Smoke

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm sewers and ditches that lead to waterways. Do not flush to sewer.

VII. HANDLING AND STORAGE

Handling Precautions:	Mildly irritating material. Avoid unnecessary exposure.
Storage Conditions:	Store in a cool dry place. Isolate from incompatible materials.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.
Respirator Type(s):	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.
Eye Protection:	No special requirements under normal industrial use.
Skin Protection:	Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water

Safety Data Sheet

before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile, Polyvinyl chloride, Impervious rubber

Chemical Name	Occupational Exposure Limits	Value
Oil mist, mineral	OSHA PEL	5 mg/m3
Oil mist, mineral	OSHA PEL	5 mg/m3
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OSHA PEL	5 mg/m3
Oil mist, mineral	ACGIH TLV-TWA	5 mg/m3
Oil mist, mineral	ACGIH TLV-TWA	5 mg/m3
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ACGIH TLV-TWA	5 mg/m3
Oil mist, mineral	ACGIH STEL	10 mg/m3
Oil mist, mineral	ACGIH STEL	10 mg/m3
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ACGIH STEL	10 mg/m3
None.	IDLH	
None.	OSHA PEL-Skin Notation	

X. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Amber
Odor:	Mild
pH:	Not determined
Viscosity (cSt at 40°C):	47.61
Solubility in Water:	Negligible; 0-1%
Octanol/Water Partition Coefficient:	Not determined
Evaporation Rate:	Not determined
Vapor Density:	Not determined
Vapor Pressure:	<0.20
Boiling Point (°C):	Not determined
Freezing Point (°C):	Not determined
Specific Gravity:	0.86
Density:	7.19
Flash Point (°C):	206
Flash Point Method:	COC
Upper Flammability Limit, % in air:	= 10
Lower Flammability Limit, % in air:	= 1

X. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Materials to Avoid:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes, and other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present.
Hazardous Polymerization:	Hazardous polymerization will not occur.

Safety Data Sheet

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion:	No hazard in normal industrial use.
Inhalation:	No hazard in normal industrial use.
Absorption:	No absorption hazard in normal industrial use.
Eyes:	This material is estimated to be non-irritating eyes (Draize score <15 [rabbits]).
Skin:	This material is likely to be slightly irritating to skin based on animal data.
Sensitization:	No data available to indicate product or components may be a skin sensitizer.

Component Toxicology Data:

Chemical Name	CAS #	LD ₅₀ /LC ₅₀
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Inhalation LC ₅₀ Rat 2.18 mg/L 4 h; Oral LD ₅₀ Rat >2000 mg/kg; Dermal LD ₅₀ Rabbit >2000 mg/kg
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	Inhalation LC ₅₀ Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD ₅₀ Rat >5000 mg/kg (Source: IUCLID); Dermal LD ₅₀ Rabbit >2000 mg/kg (Source: IUCLID)

XII. ECOLOGICAL INFORMATION

Mobility:	This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types. {EMSFORM_12MOBA}
Bioconcentration:	Bioconcentration may occur.
Degradability:	Biodegrades slowly.

Toxicity to Aquatic Invertebrates:	CAS #	Results
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC ₅₀ Daphnia magna: >1000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	48 Hr EC ₅₀ Daphnia magna: >1000 mg/L
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	48 Hr EC ₅₀ Daphnia magna: >1000 mg/L

Toxicity to Fish:	CAS #	Results
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC ₅₀ Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	96 Hr LC ₅₀ Oncorhynchus mykiss: >5000 mg/L
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	96 Hr LC ₅₀ Oncorhynchus mykiss: >5000 mg/L

XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging:	Recycle containers whenever possible.
Disposal Methods:	Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

XIV. TRANSPORTATION INFORMATION

D.O.T.	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).
---------------	--

Safety Data Sheet

XV. REGULATORY INFORMATION

TSCA Status: All components of this material are on the US TSCA Inventory or are exempt.
State Restrictions: Not applicable
WHMIS: Uncontrolled product according to WHMIS classification criteria.

Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		
None.	SARA 313		
None.	SARA 302-EHS		
None.	TSCA 12b export notification		
None.	CA Prop 65 – Cancer		
None.	CA Prop 65 - Dev. Toxicity		
None.	CA Prop 65 - Reprod –fem		
None.	CA Prop 65 - Reprod –male		
None.	Canadian WHMIS List		
None.	Massachusetts RTK List		
None.	New Jersey RTK List		
None.	Pennsylvania RTK List		
None.	Minnesota Hazardous Substance List		

Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

Safety Data Sheet

XVI. ADDITIONAL INFORMATION

Supersedes: 3/25/2015 3:27:02 PM

Revision Date: 3/25/2015 3:48:27 PM

References: ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CFR: Code of Federal Regulations

DOT: United States Department of Transportation

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

IATA: International Air Transportation Association

IDLH: Immediately Dangerous to Life or Health

IMDG: International Maritime Dangerous Goods

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit

RTK: Right-to-Know

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limit

TLV: Threshold limit value

TSCA: Toxic Substances Control Act

TWA: Time weighted average

UN: United Nations

WHMIS: Workplace Hazardous Materials Information System

Disclaimer:

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.